



SELF-CONTAINED DIRECT DRAW
1 Door Model



eco friendly
R290 Hydrocarbon
Refrigerant

JOB	
AREA	
ITEM NO.	
MODEL NO.	

MODELS
DDS36-BS-L-STK

Note: NSF/ANSI Standard 7 Listed for the storage and display of bottled or canned products only.



DDS36-BS-L-STK

KEY PRODUCT FEATURES AND BENEFITS

- Environmentally friendly and energy efficient self-contained R290 Hydrocarbon refrigeration system provides industry leading cooling performance and temperature consistency
- Reinforced bumpers on door sills protect frame while loading kegs for life long durability
- 2" foamed-in-place eco-friendly insulation provides energy savings with zero ozone depletion
- End wall compressor and evaporator design increases storage capacity by 14% compared to top mounted designs
- Full stainless steel drainer can be plumbed directly to floor drain
- Anti-sweat heaters in cabinet face prevents condensation from forming on door, extending door gasket life and protecting flooring below from damage or slip hazards

Quick Features:

- Integrated door locks standard on all units
- NSF rated digital controller allows for easy and precise temperature changes
- 6000K white LED lighting
- 1 Year Parts and Labor Warranty, 5 Year Compressor Warranty
- Made in USA



SELF-CONTAINED DIRECT DRAW
1 Door Model

MODEL NUMBERS - DDS36-BS-L-STK

MODEL NUMBERS		DDS36-BS-L-STK
NUMBER OF DOORS		1
EXTERIOR CABINET DIMENSIONS	Length - in. (mm)	36 (914)
	Depth - in. (mm)	24¾ (629)
	Height - in. (mm)	34⅝ (878)
INTERIOR CABINET DIMENSIONS	Length - in. (mm)	20 (508)
	Depth - in. (mm)	18¾ (476)
	Height - in. (mm)	31 (787)
* INTERNAL VOLUME, Net. Cu. Ft. (liters)		7.4 (210)
SHIPPING WEIGHT, Lbs. (kg.)		227 (102)
ELECTRICAL SPECIFICATIONS	Electrical Supply	120 VAC/60 Hz/1 Ph
	Running Load Amps	1.8
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 5-15
	Cord Length	6'5"
	Defrost Initiation	Automatic
	Defrost Type	Off cycle
	Thermostat	Digital control
REFRIGERATION SPECIFICATIONS	Horsepower	1/6
	Refrigerant	R290
	Refrigerant Charge (grams)	90
	Factory Temperature Setting - Refrigerator F (C)	38° (3.3°)
	Temperature Range - Refrigerator F (C)	33°-40° (0.5°-4.5°)
	Condensing Unit Location	Left or Right
	Expansion Device	Capillary tube
	Pull-Out Condensing Unit	Yes
	Front Vented	Yes
PLUMBING	Floor Drain Included	Yes
	Evaporator Condensate	Automatically

* Note: For keg capacities and layouts, go to www.perlick.com.



SELF-CONTAINED DIRECT DRAW
1 Door Model

Note: All Dispensing Towers shown are optional and must be ordered separately.

