

Camshelving®

Mobile - Starter Units with Casters with Camguard™ antimicrobial

4 Shelf Units, Vented Shelf Plates only

2 Post Heights (with 5" (12,7 cm) Casters)

67" (170,2 cm) and 75" (190,5 cm)

3 Shelf Widths

18" (45,7 cm), 21" (53,3) and 24" (61 cm)

3 Shelf Lengths

36", 42", 48" (91,4 cm, 106,7 cm, 121,9 cm)



• Starter Unit includes:

- Two Post Kits for Mobile Units.
- Four Shelf Kits.
- Four Premium or Standard Casters.

*Note: For High Density Camshelving systems order 4 Premium Swivel Locking Casters by designating (HD) at the end of the Starter Unit product codes.

Case Pack: One carton contains all components to build one unit.

Features & Benefits

Versatile Storage

Rolls smoothly into any environment, indoors or outdoors, including walk-in coolers and freezers, dry storage, wet areas or front of the house display. Works in temperatures down to -36°F (-30°C) or warm environments up to 190° F (88°C). Weldless and rust free.

Completely Mobile

Mobile Starter Units include two Premium Total Locking Casters and two Premium Swivel Locking Casters or two Standard Swivel Chrome Casters and two Swivel Chrome with Brake Casters. Premium Casters are made with a zinc plated post and non-marking polyurethane wheel. Premium Casters can be used in wet areas or in walk-in refrigerators and freezers. Standard casters are chrome plated and can be used for dry storage. Premium Swivel Locking Caster has a locking stem that locks in one direction for rigid positioning. Use four Swivel Locking Casters to create High Density Camshelving systems. The caster controls the direction the unit travels in, eliminating the need for stationary rail tracking. The Premium Total Locking Caster has a brake that locks both the motion and the swivel when set in place. Use two Total Locking Casters and two Swivel Locking Casters for standard Mobile Camshelving Units.

Easy to Clean

Camshelving shelf plates contain Camguard™ antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing. The traverses and post kits are smooth polypropylene so they can be wiped or steam cleaned. The traverses can be easily removed and washed in a conveyor dishwasher.

Easy to Assemble

Assembles in minutes with the use of a rubber mallet. Requires no bolts or nuts, clips or stainless steel connectors. Molded in dovetails on posts ensure that traverses set easily into place.

Item No. _____

Specifier Identification No. _____

Code No. _____


Quantity _____



Mobile Camshelving Unit.



Premium Casters.



Standard Casters.

Strong as Steel

Posts and traverses are made of a steel core coated with polypropylene. Uniquely engineered post connectors offer exceptional cross stabilization. Casters are made of reinforced nylon. Maximum weight-bearing capacity of 750 pounds (340 kg) per mobile unit.

Easy to Adjust

Requires use of rubber mallet. Shelves can be adjusted at 4" (10,2 cm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit.

Optional Accessories

Place the 3/2" (8,9 cm) rubber Donut Bumper over the top of the Caster before placing the Caster in the Post. Protects walls and other pieces of equipment from being damaged during mobile unit transport. Identification Tags clip easily onto traverses.

Approvals



Components * Does not include 6" (15 cm) Shelf Plate.

Mobile - Starter Units with Casters 4 Shelf Units, Vented Shelf Plates only

FOUR SHELF STARTER UNIT

for Mobile Camshelving includes two Post Kits for Mobile Units, four Vented Shelf Kits, two Premium Total Locking Casters and two Swivel Locking Casters or two Standard Swivel Chrome Casters and two Swivel Chrome with Brake.

67" (170,2 cm) Height 18" (45,7 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSUR48366	CSURS48366	36" 91,4	87.36 (5.90)	39,63 (0,1671)
CSUR48426	CSURS48426	42" 106,7	96.08 (5.90)	43,58 (0,1671)
CSUR48486	CSURS48486	48" 121,9	101.36 (5.90)	45,98 (0,1671)

75" (190,5 cm) Height 18" (45,7 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSUR48367	CSURS48367	36" 91,4	89.46 (5.90)	40,58 (0,1671)
CSUR48427	CSURS48427	42" 106,7	98.18 (5.90)	44,53 (0,1671)
CSUR48487	CSURS48487	48" 121,9	103.46 (5.90)	46,93 (0,1671)

67" (170,2 cm) Height 21" (53,3 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSUR41366	CSURS41366	36" 91,4	90.92 (7.17)	43,29 (0,2030)
CSUR41426	CSURS41426	42" 106,7	101.12 (7.17)	45,82 (0,2030)
CSUR41486	CSURS41486	48" 121,9	106.96 (7.17)	48,51 (0,2030)

75" (190,5 cm) Height 21" (53,3 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSUR41367	CSURS41367	36" 91,4	94.42 (7.17)	42,83 (0,2030)
CSUR41427	CSURS41427	42" 106,7	104.62 (7.17)	47,45 (0,2030)
CSUR41487	CSURS41487	48" 121,9	110.46 (7.17)	50,10 (0,2030)

67" (170,2 cm) Height 24" (61 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSUR44366	CSURS44366	36" 91,4	95.44 (8.50)	43,29 (0,2407)
CSUR44426	CSURS44426	42" 106,7	104.24 (8.50)	47,28 (0,2407)
CSUR44486	CSURS44486	48" 121,9	113.00 (8.50)	51,26 (0,2407)

75" (190,5 cm) Height 24" (61 cm) Width

Premium caster code	Standard caster code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSUR44367	CSURS44367	36" 91,4	98.94 (8.50)	44,88 (0,2407)
CSUR44427	CSURS44427	42" 106,7	107.74 (8.50)	48,87 (0,2407)
CSUR44487	CSURS44487	48" 121,9	116.50 (8.50)	52,84 (0,2407)

NOTE: For High Density Camshelving systems order 4 Premium Swivel Locking Casters by designating (HD) at the end of the Starter Unit product codes.

Architect Specs

Posts:	Internal steel core, reinforced polypropylene exterior.
Post Connectors:	Reinforced polypropylene.
Traverses:	Internal steel core, reinforced polypropylene exterior.
Vented/Solid Shelf Plates:	Reinforced polypropylene with Camguard™ antimicrobial.
Premium Casters:	Reinforced nylon with zinc plated post and thermoplastic rubber wheels.
Standard Casters:	Chrome plated with rubber wheels.

Optional Accessories

- Donut Bumper for Caster CSRDB Color: Dark Gray Case pack: 4 each
 Identification Tag 6" CSID Color: White/Clear Case pack: 12 each
 Identification Tag 3" CSID3 Color: White/Clear Case pack: 12 each

Standard Colors

- Speckled Gray (480)

Approvals



Components * Does not include 6" (15 cm) Shelf Plate.